

EPA203_B2

Safety Data Sheet INTERCURE 200HS SAND PART A

Bulk Sales Reference No.: EPA203
SDS Revision Date: 01/15/2019
SDS Revision Number: B2-5



1. Identification of the preparation and company

1.1. Product identifier

Product Identity INTERCURE 200HS SAND PART A

Bulk Sales Reference No. EPA203

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC
Manufacturer:
Akzo Nobel Coatings
International Paint
6001 Antoine Drive
Houston, Texas 77091

Emergency

CHEMTREC (800) 424-9300

International Paint (713) 682-1711

Poison Control Center (800) 854-6813

Customer Service

International Paint (800) 589-1267

Fax No. (800) 631-7481

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.

Skin Irrit. 2;H315 Causes skin irritation.

Eye Irrit. 2;H319 Causes serious eye irritation.

Skin Sens. 1;H317 May cause an allergic skin reaction.

Carc. 1A;H350 May cause cancer.

STOT RE 2;H373 May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 1;H410 Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Danger.

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.
 H350 May cause cancer.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H410 Very toxic to aquatic life with long lasting effects.

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.
 P235 Keep cool.
 P240 Ground / bond container and receiving equipment.
 P241 Use explosion-proof electrical / ventilating / light / equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe mist / vapors / spray.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves / eye protection / face protection.
 P302+352 IF ON SKIN: Wash with soap and water.
 P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
 P308+313 IF exposed or concerned: Get medical advice/attention.
 P314 Get Medical advice / attention if you feel unwell.
 P333 If skin irritation or a rash occurs:.
 P337 If eye irritation persists:.
 P362 Take off contaminated clothing and wash before reuse.
 P363 Wash contaminated clothing before reuse.
 P370 In case of fire: Use water spray, fog, or regular foam..
 P391 Collect spillage.
 P403+233 Store in a well ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating Health: 2* Flammability: 2 Reactivity: 0

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Bisphenol A - Epichlorohydrin polymer CAS Number: 0025068-38-6	10 - 25	Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Chronic 2;H411	[1]
Nepheline syenite CAS Number: 0037244-96-5	10 - 25	Combustible Dust	[1]
Magnesium silicate talc CAS Number: 0014807-96-6	10 - 25	Not Classified	[1][2]
Phosphoric acid, zinc salt (2:3) CAS Number: 0007779-90-0	10 - 25	Aquatic Acute 1;H400 Aquatic Chronic 1;H410	[1]
Titanium dioxide CAS Number: 0013463-67-7	1.0 - 10	Not Classified	[1][2]
Xylene CAS Number: 0001330-20-7	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315	[1][2]

EPA203_B2

EPOXY RESIN CAS Number: 0025036-25-3	1.0 - 10	Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317	[1]
Cashew, nutshell liquid, polymer with epichlorohydrin CAS Number: 0068413-24-1	1.0 - 10	----	[1]
1-Methoxy-2-propanol CAS Number: 0000107-98-2	1.0 - 10	Flam. Liq. 3;H226 STOT SE 3;H336	[1][2]
Ferric oxide hydroxide CAS Number: 0020344-49-4	1.0 - 10	No Classification	[1]
Benzyl alcohol CAS Number: 0000100-51-6	1.0 - 10	Acute Tox. 4;H332 Acute Tox. 4;H302	[1]
Ethyl Benzene CAS Number: 0000100-41-4	1.0 - 10	Flam. Liq. 2;H225 Acute Tox. 4;H332 STOT RE 2;H373 Asp. Tox. 1;H304	[1][2]
Crystalline Silica - Quartz CAS Number: 0014808-60-7	0.10 - 1.0	Acute Tox. 4;H332 STOT RE 2;H373 Carc. 1A;H350	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.

Chronic effects

5. Fire-fighting measures

5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient.
 CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective.
 SMALL FIRES: Use dry chemical, CO₂, water spray or regular foam. LARGE FIRES: Use water spray, fog, or regular foam. Do not use straight streams. Move containers from fire area if you can do so without risk.

5.2. Special hazards arising from the substance or mixture

No data available

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 128

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

7. Handling and storage

7.1. Precautions for safe handling

Handling

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

In Storage

Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Do not get in eyes, on skin or clothing.

No data available

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000100-41-4	Ethyl Benzene	OSHA	100 ppm TWA; 435 mg/m ³ TWA 125 ppm STEL; 545 mg/m ³ STEL
		ACGIH	20 ppm TWA
		NIOSH	100 ppm TWA; 435 mg/m ³ TWA 125 ppm STEL; 545 mg/m ³ STEL 800 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	20 ppm TWA
		Mexico	20 ppm TWA VLE-PPT
		Brazil	78 ppm TWA LT; 340 mg/m ³ TWA LT

EPA203_B2

0000100-51-6	Benzyl alcohol	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000107-98-2	1-Methoxy-2-propanol	OSHA	150 ppm STEL; 540 mg/m3 STEL
		ACGIH	50 ppm TWA100 ppm STEL
		NIOSH	100 ppm TWA; 360 mg/m3 TWA150 ppm STEL; 540 mg/m3 STEL
		Supplier	No Established Limit
		OHSA, CAN	50 ppm TWA100 ppm STEL
		Mexico	100 ppm TWA VLE-PPT150 ppm STEL [PPT-CT]
		Brazil	No Established Limit
0001330-20-7	Xylene	OSHA	100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL
		ACGIH	100 ppm TWA150 ppm STEL
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	100 ppm TWA150 ppm STEL
		Mexico	100 ppm TWA VLE-PPT150 ppm STEL [PPT-CT]
		Brazil	78 ppm TWA LT; 340 mg/m3 TWA LT
0007779-90-0	Phosphoric acid, zinc salt (2:3)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0013463-67-7	Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	2.4 mg/m3 TWA (CIB 63, fine); 0.3 mg/m3 TWA (CIB 63, ultrafine, including engineered nanoscale)5000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA
		Mexico	10 mg/m3 TWA VLE-PPT
		Brazil	No Established Limit
0014807-96-6	Magnesium silicate talc	OSHA	No Established Limit
		ACGIH	2 mg/m3 TWA (particulate matter containing no asbestos and
		NIOSH	2 mg/m3 TWA (containing no Asbestos and
		Supplier	No Established Limit
		OHSA, CAN	2 mg/m3 TWA (containing no Asbestos and
		Mexico	2 mg/m3 TWA VLE-PPT (particulate matter containing no asbestos and
		Brazil	No Established Limit
0014808-60-7	Crystalline Silica - Quartz	OSHA	50 ug/m3 TWA (listed under Respirable crystalline silica)
		ACGIH	0.025 mg/m3 TWA (respirable particulate matter)
		NIOSH	0.05 mg/m3 TWA (respirable dust)50 mg/m3 IDLH (respirable dust)

EPA203_B2

		Supplier	No Established Limit
		OHSA, CAN	0.10 mg/m3 TWA (designated substances regulation, respirable, listed under Silica, crystalline)0.10 mg/m3 TWA (respirable fraction, listed under Silica, crystalline)
		Mexico	0.025 mg/m3 TWA VLE-PPT (respirable fraction)
		Brazil	No Established Limit
0020344-49-4	Ferric oxide hydroxide	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0025036-25-3	EPOXY RESIN	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0025068-38-6	Bisphenol A - Epichlorohydrin polymer	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0037244-96-5	Nepheline syenite	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA (total dust)
		Mexico	No Established Limit
		Brazil	No Established Limit
0068413-24-1	Cashew, nutshell liquid, polymer with epichlorohydrin	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
0000100-41-4	Ethyl Benzene	NIOSH	Eye skin
0000100-51-6	Benzyl alcohol	NIOSH	No Established Limit
0000107-98-2	1-Methoxy-2-propanol	NIOSH	Eye nose
0001330-20-7	Xylene	NIOSH	Central nervous system depressant; respiratory and eye irritation
0007779-90-0	Phosphoric acid, zinc salt (2:3)	NIOSH	No Established Limit
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0014807-96-6	Magnesium silicate talc	NIOSH	(containing asbestos); Fibrotic pneumoconiosis; (containing no

EPA203_B2

			asbestos); Nonmalignant respiratory effects
0014808-60-7	Crystalline Silica - Quartz	NIOSH	Chronic lung disease (silicosis)
0020344-49-4	Ferric oxide hydroxide	NIOSH	No Established Limit
0025036-25-3	EPOXY RESIN	NIOSH	No Established Limit
0025068-38-6	Bisphenol A - Epichlorohydrin polymer	NIOSH	No Established Limit
0037244-96-5	Nepheline syenite	NIOSH	No Established Limit
0068413-24-1	Cashew, nutshell liquid, polymer with epichlorohydrin	NIOSH	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000100-41-4	Ethyl Benzene	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0000100-51-6	Benzyl alcohol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000107-98-2	1-Methoxy-2-propanol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001330-20-7	Xylene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0007779-90-0	Phosphoric acid, zinc salt (2:3)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0014807-96-6	Magnesium silicate talc	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0014808-60-7	Crystalline Silica - Quartz	OSHA	Select Carcinogen: Yes
		NTP	Known: Yes; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0020344-49-4	Ferric oxide hydroxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0025036-25-3	EPOXY RESIN	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0025068-38-6	Bisphenol A - Epichlorohydrin polymer	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0037244-96-5	Nepheline syenite	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;

EPA203_B2

			Group 4: No;
0068413-24-1	Cashew, nutshell liquid, polymer with epichlorohydrin	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Appearance	Coloured Liquid
Odor threshold	Not Measured
pH	No Established Limit
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	117 (°C) 243 (°F)
Flash Point	38 (°C) 100 (°F)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1 Upper Explosive Limit: No Established Limit
vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than air
Specific Gravity	1.92
Solubility in Water	Not Measured
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	No Established Limit Not Measured
VOC %	Refer to the Technical Data Sheet or label where information is available.

10. Stability and reactivity

EPA203_B2

10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

11. Toxicological information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr
Bisphenol A - Epichlorohydrin polymer - (25068-38-6)	5,001.00, Rat - Category: NA	20,000.00, Rabbit - Category: NA	No data available	No data available
Nepheline syenite - (37244-96-5)	No data available	No data available	No data available	No data available
Magnesium silicate talc - (14807-96-6)	No data available	No data available	No data available	No data available
Phosphoric acid, zinc salt (2:3) - (7779-90-0)	5,001.00, Rat - Category: NA	No data available	No data available	No data available
Titanium dioxide - (13463-67-7)	5,001.00, Mouse - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA
Xylene - (1330-20-7)	4,299.00, Rat - Category: 5	1,548.00, Rabbit - Category: 4	No data available	20.00, Rat - Category: NA
EPOXY RESIN - (25036-25-3)	No data available	No data available	No data available	No data available
Cashew, nutshell liquid, polymer with epichlorohydrin - (68413-24-1)	No data available	No data available	No data available	No data available
1-Methoxy-2-propanol - (107-98-2)	5,000.00, Rat - Category: 5	13,000.00, Rabbit - Category: NA	No data available	No data available
Ferric oxide hydroxide - (20344-49-4)	5,000.00, Rat - Category: 5	No data available	No data available	No data available
Benzyl alcohol - (100-51-6)	1,570.00, Rat - Category: 4	2,000.00, Rabbit - Category: 4	No data available	4.178, Rat - Category: 4
Ethyl Benzene - (100-41-4)	3,500.00, Rat - Category: 5	15,433.00, Rabbit - Category: NA	17.20, Rat - Category: 4	No data available
Crystalline Silica - Quartz - (14808-60-7)	No data available	No data available	No data available	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable

EPA203_B2

Skin corrosion/irritation	2	Causes skin irritation.
Eye damage/irritation	2	Causes serious eye irritation.
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	1A	May cause cancer.
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not Classified	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Bisphenol A - Epichlorohydrin polymer - (25068-38-6)	3.10, Pimephales promelas	1.40, Daphnia magna	Not Available
Nepheline syenite - (37244-96-5)	Not Available	Not Available	Not Available
Magnesium silicate talc - (14807-96-6)	Not Available	Not Available	Not Available
Phosphoric acid, zinc salt (2:3) - (7779-90-0)	0.09, Oncorhynchus mykiss	0.04, Daphnia magna	0.136 (72 hr), Selenastrum capricornutum
Titanium dioxide - (13463-67-7)	294.00, Oryzias latipes	501.00, Daphnia magna	51.00 (72 hr), Pseudokirchnerella subcapitata
Xylene - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
EPOXY RESIN - (25036-25-3)	Not Available	Not Available	Not Available
Cashew, nutshell liquid, polymer with epichlorohydrin - (68413-24-1)	Not Available	Not Available	Not Available
1-Methoxy-2-propanol - (107-98-2)	1,000.00, Oncorhynchus mykiss	500.00, Daphnia magna	1,000.00 (96 hr), Selenastrum capricornutum
Ferric oxide hydroxide - (20344-49-4)	1,000.00, Leuciscus idus	Not Available	Not Available
Benzyl alcohol - (100-51-6)	460.00, Pimephales promelas	230.00, Daphnia magna	770.00 (72 hr), Pseudokirchnerella subcapitata
Ethyl Benzene - (100-41-4)	4.20, Oncorhynchus mykiss	2.93, Daphnia magna	3.60 (96 hr), Pseudokirchnerella subcapitata
Crystalline Silica - Quartz - (14808-60-7)	Not Available	Not Available	0.00 (hr),

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

14.1. UN number UN 1263

14.2. UN proper shipping name PAINT

14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)		IMO / IMDG (Ocean Transportation)	
Proper Shipping Name	PAINT	IMDG Proper Shipping Name	PAINT
Hazard Class	3 - Flammable	IMDG Hazard Class Sub Class	3 - Flammable Not applicable
UN / NA Number	UN 1263	IMDG Packing Group	III
Packing Group	III	System Reference Code	2
CERCLA/DOT RQ	116 gal. / 1861 lbs.		

14.4. Packing group III

14.5. Environmental hazards

IMDG Marine Pollutant: Yes (Phosphoric acid, zinc salt (2:3))

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B3 D2A

DOT Marine Pollutants (10%):
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :
Ethyl Benzene (1000 lb final RQ; 454 kg final RQ)
Xylene (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :

Ethyl Benzene
 Xylene
 Mass RTK Substances (>1%) :
 1-Methoxy-2-propanol
 Benzyl alcohol
 Ethyl Benzene
 Magnesium silicate talc
 Titanium dioxide
 Xylene
 Penn RTK Substances (>1%) :
 1-Methoxy-2-propanol
 Benzyl alcohol
 Ethyl Benzene
 Magnesium silicate talc
 Titanium dioxide
 Xylene
 Penn Special Hazardous Substances (>.01%) :
 (No Product Ingredients Listed)
 RCRA Status:
 (No Product Ingredients Listed)
 N.J. RTK Substances (>1%) :
 1-Methoxy-2-propanol
 Ethyl Benzene
 Magnesium silicate talc
 Titanium dioxide
 Xylene
 N.J. Special Hazardous Substances (>.01%) :
 1-Methoxy-2-propanol
 Crystalline Silica - Quartz
 Ethyl Benzene
 Magnesium silicate talc
 Xylene
 N.J. Env. Hazardous Substances (>.1%) :
 Ethyl Benzene
 Xylene
 Proposition 65 - Carcinogens (>0%):
 Benzene
 Naphthalene
 Ethyl Benzene
 1-CHLORO-2,3-EPOXY PROPANE
 Nickel
 Titanium dioxide
 Proposition 65 - Female Repro Toxins (>0%):
 (No Product Ingredients Listed)
 Proposition 65 - Male Repro Toxins (>0%):
 Benzene
 1-CHLORO-2,3-EPOXY PROPANE
 Proposition 65 - Developmental Toxins (>0%):
 Benzene

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.
H226 Flammable liquid and vapor.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H350 May cause cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

The following sections have changed since the previous revision.

SECTION 12: Ecological information

End of Document