

Safety Data Sheet
 INTERGARD 264 BLACK PART A

Bulk Sales Reference No.: FPY999
 SDS Revision Date: 03/29/2019
 SDS Revision Number: P6-5



1. Identification of the preparation and company

1.1. Product identifier

Product Identity INTERGARD 264 BLACK PART A
 Bulk Sales Reference No. FPY999

1.2. Relevant identified uses of the substance or mixture and uses advised against
 Intended Use See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC
 Manufacturer:
 Akzo Nobel Coatings
 International Paint
 6001 Antoine Drive
 Houston, Texas 77091

Emergency
 CHEMTREC (800) 424-9300
 International Paint (713) 682-1711
 Poison Control Center (800) 854-6813
 Customer Service
 International Paint (800) 589-1267
 Fax No. (800) 631-7481

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.
 Skin Irrit. 2;H315 Causes skin irritation.
 Eye Irrit. 2;H319 Causes serious eye irritation.
 Skin Sens. 1;H317 May cause an allergic skin reaction.
 Aquatic Chronic 2;H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Warning.

H226 Flammable liquid and vapor.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H411 Toxic to aquatic life with long lasting effects.

- P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.
- P235 Keep cool.
- P240 Ground / bond container and receiving equipment.
- P241 Use explosion-proof electrical / ventilating / light / equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
- P264 Wash area of contact thoroughly after handling.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves / eye protection / face protection.
- P302+352 IF ON SKIN: Wash with soap and water.
- P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
- P333+313 If skin irritation or a rash occurs: Get medical advice/attention.
- P337+313 If eye irritation persists: Get medical advice / attention.
- P362 Take off contaminated clothing and wash before reuse.
- P363 Wash contaminated clothing before reuse.
- P370 In case of fire: Use water spray, fog, or regular foam..
- P391 Collect spillage.
- P403+233 Store in a well ventilated place. Keep container tightly closed.
- P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating Health: 2* Flammability: 2 Reactivity: 0

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations | Weight % | GHS Classification | Notes |
|---|----------|--|--------|
| Magnesium silicate talc CAS Number: 0014807-96-6 | 25 - 50 | Not Classified | [1][2] |
| Barium sulfate CAS Number: 0007727-43-7 | 25 - 50 | Not Classified | [1][2] |
| Bisphenol A - Epichlorohydrin polymer CAS Number: 0025068-38-6 | 10 - 25 | Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Chronic 2;H411 | [1] |
| p-Chloro-a,a,a-trifluorotoluene CAS Number: 0000098-56-6 | 1.0 - 10 | Flam. Liq. 3;H226 Skin Irrit. 2;H315 Eye Irrit. 2;H319 STOT SE 3;H335 | [1] |
| EPOXY RESIN CAS Number: 0025036-25-3 | 1.0 - 10 | Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317 | [1] |
| Benzyl alcohol CAS Number: 0000100-51-6 | 1.0 - 10 | Acute Tox. 4;H332 Acute Tox. 4;H302 Eye Irrit. 2;H319 | [1] |
| Solvent naphtha (petroleum), light aromatic CAS Number: 0064742-95-6 | 1.0 - 10 | Asp. Tox. 1;H304 | [1] |
| Methyl Amyl Ketone CAS Number: 0000110-43-0 | 1.0 - 10 | Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H302 | [1][2] |
| 1,2,4-trimethyl benzene CAS Number: 0000095-63-6 | 1.0 - 10 | Flam. Liq. 3;H226 Acute Tox. 4;H332 Eye Irrit. 2;H319 | [1] |

| | | | |
|--|----------|---|--------|
| | | STOT SE 3;H335 Skin Irrit. 2;H315 Aquatic Chronic 2;H411 | |
| Carbon black CAS Number: 0001333-86-4 | 1.0 - 10 | Not Classified | [1][2] |

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

| |
|-----------------------|
| 4. First aid measures |
|-----------------------|

4.1. Description of first aid measures

| | |
|------------|---|
| General | Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes. |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. |
| Eyes | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. |
| Skin | In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately. |
| Ingestion | If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|------------|--|
| Overview | NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing. |
| Inhalation | Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea. |
| Eyes | Causes severe eye irritation. Avoid contact with eyes. |
| Skin | Causes skin irritation. May be harmful if absorbed through the skin. |
| Ingestion | Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness. |

| |
|---------------------------|
| 5. Fire-fighting measures |
|---------------------------|

5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient.
 CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective.
 SMALL FIRES: Use dry chemical, CO₂, water spray or regular foam. LARGE FIRES: Use water spray, fog, or regular foam. Do not use straight streams. Move containers from fire area if you can do so without risk.

5.2. Special hazards arising from the substance or mixture

No data available

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 128

| |
|--------------------------------|
| 6. Accidental release measures |
|--------------------------------|

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

| |
|--------------------------------|
| 7. Handling and storage |
|--------------------------------|

7.1. Precautions for safe handling

Handling

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

In Storage

Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Avoid contact with eyes, skin and clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

| |
|---|
| 8. Exposure controls and personal protection |
|---|

8.1. Control parameters

Exposure

| CAS No. | Ingredient | Source | Value |
|--------------|---------------------------------|-----------|---------------------------|
| 0000095-63-6 | 1,2,4-trimethyl benzene | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | 25 ppm TWA; 125 mg/m3 TWA |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0000098-56-6 | p-Chloro-a,a,a-trifluorotoluene | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0000100-51-6 | Benzyl alcohol | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |

FPY999_P6

| | | | |
|--------------|---|-----------|--|
| 0000110-43-0 | Methyl Amyl Ketone | OSHA | 100 ppm TWA; 465 mg/m3 TWA |
| | | ACGIH | 50 ppm TWA |
| | | NIOSH | 100 ppm TWA; 465 mg/m3 TWA800 ppm IDLH |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 25 ppm TWA; 115 mg/m3 TWA |
| | | Mexico | 50 ppm TWA VLE-PPT |
| | | Brazil | No Established Limit |
| 0001333-86-4 | Carbon black | OSHA | 3.5 mg/m3 TWA |
| | | ACGIH | 3 mg/m3 TWA (inhalable particulate matter) |
| | | NIOSH | 3.5 mg/m3 TWA; 0.1 mg/m3 TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as 1750 mg/m3 IDLH |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 3 mg/m3 TWA (inhalable) |
| | | Mexico | 3 mg/m3 TWA VLE-PPT (inhalable fraction) |
| | | Brazil | No Established Limit |
| 0007727-43-7 | Barium sulfate | OSHA | 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction) |
| | | ACGIH | 5 mg/m3 TWA (inhalable particulate matter, particulate matter containing no asbestos and |
| | | NIOSH | 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust) |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 5 mg/m3 TWA (particulate matter containing no Asbestos and |
| | | Mexico | 10 mg/m3 TWA VLE-PPT |
| | | Brazil | No Established Limit |
| 0014807-96-6 | Magnesium silicate talc | OSHA | No Established Limit |
| | | ACGIH | 2 mg/m3 TWA (particulate matter containing no asbestos and |
| | | NIOSH | 2 mg/m3 TWA (containing no Asbestos and |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 2 mg/m3 TWA (containing no Asbestos and |
| | | Mexico | 2 mg/m3 TWA VLE-PPT (particulate matter containing no asbestos and |
| | | Brazil | No Established Limit |
| 0025036-25-3 | EPOXY RESIN | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0025068-38-6 | Bisphenol A - Epichlorohydrin polymer | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0064742-95-6 | Solvent naphtha (petroleum), light aromatic | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | Supplier | No Established Limit |

FPY999_P6

| | | |
|--|-----------|----------------------|
| | OSHA, CAN | No Established Limit |
| | Mexico | No Established Limit |
| | Brazil | No Established Limit |

Health Data

| CAS No. | Ingredient | Source | Value |
|--------------|---|--------|--|
| 0000095-63-6 | 1,2,4-trimethyl benzene | NIOSH | No Established Limit |
| 0000098-56-6 | p-Chloro-a,a,a-trifluorotoluene | NIOSH | No Established Limit |
| 0000100-51-6 | Benzyl alcohol | NIOSH | No Established Limit |
| 0000110-43-0 | Methyl Amyl Ketone | NIOSH | Irritation; liver kidney |
| 0001333-86-4 | Carbon black | NIOSH | Lung cardiovascular |
| 0007727-43-7 | Barium sulfate | NIOSH | Eye nose |
| 0014807-96-6 | Magnesium silicate talc | NIOSH | (containing asbestos); Fibrotic pneumoconiosis; (containing no asbestos); Nonmalignant respiratory effects |
| 0025036-25-3 | EPOXY RESIN | NIOSH | No Established Limit |
| 0025068-38-6 | Bisphenol A - Epichlorohydrin polymer | NIOSH | No Established Limit |
| 0064742-95-6 | Solvent naphtha (petroleum), light aromatic | NIOSH | No Established Limit |

Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|--------------|---------------------------------------|--------|---|
| 0000095-63-6 | 1,2,4-trimethyl benzene | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000098-56-6 | p-Chloro-a,a,a-trifluorotoluene | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000100-51-6 | Benzyl alcohol | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000110-43-0 | Methyl Amyl Ketone | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0001333-86-4 | Carbon black | OSHA | Select Carcinogen: Yes |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 0007727-43-7 | Barium sulfate | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0014807-96-6 | Magnesium silicate talc | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0025036-25-3 | EPOXY RESIN | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0025068-38-6 | Bisphenol A - Epichlorohydrin polymer | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |

FPY999_P6

| | | | |
|--------------|---|------|--|
| 0064742-95-6 | Solvent naphtha (petroleum), light aromatic | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |

8.2. Exposure controls

| | |
|----------------------|---|
| Respiratory | Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet. |
| Eyes | Avoid contact with eyes. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. |
| Skin | Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products. When there is a risk of ignition from static electricity, wear antistatic protective clothing and footwear. Any additional personal protective equipment or measures should be selected based on the risk assessment of the task being performed and should be approved by a specialist before handling this product. |
| Engineering Controls | Depending on the site-specific conditions of use, provide adequate ventilation. |
| Other Work Practices | Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water. |

9. Physical and chemical properties

| | |
|---|--|
| Appearance | Coloured Liquid |
| Odor threshold | Not Measured |
| pH | No Established Limit |
| Melting point / freezing point | Not Measured |
| Initial boiling point and boiling range | 139 (°C) 282 (°F) |
| Flash Point | 47 (°C) 117 (°F) |
| Evaporation rate (Ether = 1) | Not Measured |
| Flammability (solid, gas) | Not Applicable |
| Upper/lower flammability or explosive limits | Lower Explosive Limit: .9 Upper Explosive Limit: No Established Limit |
| vapor pressure (Pa) | Not Measured |
| Vapor Density | Heavier than air |
| Specific Gravity | 1.89 |
| Solubility in Water | Not Measured |
| Partition coefficient n-octanol/water (Log Kow) | Not Measured |
| Auto-ignition temperature | Not Measured |
| Decomposition temperature | Not Measured |
| Viscosity (cSt) | No Established Limit Not Measured |
| VOC % | Refer to the Technical Data Sheet or label where information is available. |

10. Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

No data available

| |
|-------------------------------|
| 11. Toxicological information |
|-------------------------------|

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LC50, mg/L/4hr | Inhalation Dust/Mist LC50, mg/L/4hr |
|--|-------------------------------------|--|---------------------------------------|---|
| Magnesium silicate talc - (14807-96-6) | No data available | No data available | No data available | No data available |
| Barium sulfate - (7727-43-7) | 3,000.00, Mouse - Category: 5 | No data available | No data available | No data available |
| Bisphenol A - Epichlorohydrin polymer - (25068-38-6) | 5,001.00, Rat - Category: NA | 20,000.00, Rabbit - Category: NA | No data available | No data available |
| p-Chloro-a,a,a-trifluorotoluene - (98-56-6) | 13,000.00, Rat - Category: NA | No data available | 33.00, Rat - Category: NA | No data available |
| EPOXY RESIN - (25036-25-3) | No data available | No data available | No data available | No data available |
| Benzyl alcohol - (100-51-6) | 1,570.00, Rat - Category: 4 | 2,000.00, Rabbit - Category: 4 | No data available | 4.178, Rat - Category: 4 |
| Solvent naphtha (petroleum), light aromatic - (64742-95-6) | 6,800.00, Rat - Category: NA | 3,400.00, Rabbit - Category: 5 | No data available | No data available |
| Methyl Amyl Ketone - (110-43-0) | 1,670.00, Rat - Category: 4 | 12,600.00, Rat - Category: NA | No data available | No data available |
| 1,2,4-trimethyl benzene - (95-63-6) | 3,400.00, Rat - Category: 5 | 3,160.00, Rabbit - Category: 5 | 18.00, Rat - Category: 4 | No data available |
| Carbon black - (1333-86-4) | 8,001.00, Rat - Category: NA | No data available | No data available | No data available |

| Item | Category | Hazard |
|-----------------------------|----------------|--------------------------------------|
| Acute Toxicity (mouth) | Not Classified | Not Applicable |
| Acute Toxicity (skin) | Not Classified | Not Applicable |
| Acute Toxicity (inhalation) | Not Classified | Not Applicable |
| Skin corrosion/irritation | 2 | Causes skin irritation. |
| Eye damage/irritation | 2 | Causes serious eye irritation. |
| Sensitization (respiratory) | Not Classified | Not Applicable |
| Sensitization (skin) | 1 | May cause an allergic skin reaction. |
| Germ toxicity | Not Classified | Not Applicable |

FPY999_P6

| | | |
|---|----------------|----------------|
| Carcinogenicity | Not Classified | Not Applicable |
| Reproductive Toxicity | Not Classified | Not Applicable |
| Specific target organ systemic Toxicity (repeated exposure) | Not Classified | Not Applicable |
| Aspiration hazard | Not Classified | Not Applicable |

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

| Ingredient | 96 hr LC50 fish, mg/l | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l |
|--|------------------------------|----------------------------|--|
| Magnesium silicate talc - (14807-96-6) | Not Available | Not Available | Not Available |
| Barium sulfate - (7727-43-7) | 59,000.00, Poecilia sphenops | 32.00, Daphnia magna | Not Available |
| Bisphenol A - Epichlorohydrin polymer - (25068-38-6) | 3.10, Pimephales promelas | 1.40, Daphnia magna | Not Available |
| p-Chloro-a,a,a-trifluorotoluene - (98-56-6) | 11.50, Lepomis macrochirus | 3.68, Daphnia magna | Not Available |
| EPOXY RESIN - (25036-25-3) | Not Available | Not Available | Not Available |
| Benzyl alcohol - (100-51-6) | 460.00, Pimephales promelas | 230.00, Daphnia magna | 770.00 (72 hr), Pseudokirchnerella subcapitata |
| Solvent naphtha (petroleum), light aromatic - (64742-95-6) | 9.22, Oncorhynchus mykiss | 6.14, Daphnia magna | 19.00 (72 hr), Selenastrum capricornutum |
| Methyl Amyl Ketone - (110-43-0) | 131.00, Pimephales promelas | 90.20, Daphnia magna | 98.20 (72 hr), Pseudokirchneriella subcapitata |
| 1,2,4-trimethyl benzene - (95-63-6) | 7.72, Pimephales promelas | 3.60, Daphnia magna | 2.356 (96 hr), Green algae |
| Carbon black - (1333-86-4) | 1,000.00, Danio rerio | Not Available | 10,000.00 (72 hr), Scenedesmus subspicatus |

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

| |
|---------------------------|
| 14. Transport information |
|---------------------------|

14.1. UN number UN 1263
 14.2. UN proper shipping name PAINT
 14.3. Transport hazard class(es)

| DOT (Domestic Surface Transportation) | | IMO / IMDG (Ocean Transportation) | |
|---------------------------------------|------------------------|-----------------------------------|----------------|
| Proper Shipping Name | PAINT | IMDG Proper Shipping Name | PAINT |
| Hazard Class | 3 - Flammable | IMDG Hazard Class | 3 - Flammable |
| | | Sub Class | Not applicable |
| UN / NA Number | UN 1263 | IMDG Packing Group | III |
| Packing Group | III | System Reference Code | 1 |
| CERCLA/DOT RQ | 6310 gal. / 99206 lbs. | | |

14.4. Packing group III
 14.5. Environmental hazards
 IMDG Marine Pollutant: Yes (Bisphenol A - Epichlorohydrin polymer)
 14.6. Special precautions for user
 Not Applicable
 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
 Not Applicable

| |
|----------------------------|
| 15. Regulatory information |
|----------------------------|

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B3 D2B

DOT Marine Pollutants (10%):
 (No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):
 (No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :
 Xylene (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :
 (No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :
 1,2,4-trimethyl benzene
 Xylene

Mass RTK Substances (>1%) :
 1,2,4-trimethyl benzene
 Barium sulfate
 Benzyl alcohol
 Carbon black
 Magnesium silicate talc
 Methyl Amyl Ketone

Penn RTK Substances (>1%) :
 1,2,4-trimethyl benzene
 Barium sulfate
 Benzyl alcohol
 Carbon black
 Magnesium silicate talc
 Methyl Amyl Ketone

Penn Special Hazardous Substances (>.01%) :

Carbon black

RCRA Status:

(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

1,2,4-trimethyl benzene

Barium sulfate

Carbon black

Magnesium silicate talc

Methyl Amyl Ketone

N.J. Special Hazardous Substances (>.01%) :

Cumene

Carbon black

Magnesium silicate talc

Xylene

N.J. Env. Hazardous Substances (>.1%) :

1,2,4-trimethyl benzene

Xylene

Proposition 65 - Carcinogens (>0%):

Benzene

Naphthalene

p-Chloro-a,a,a-trifluorotoluene

Cumene

Ethyl Benzene

Carbon black

Proposition 65 - Female Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0%):

Benzene

Proposition 65 - Developmental Toxins (>0%):

Benzene

| |
|-----------------------|
| 16. Other information |
|-----------------------|

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

End of Document