

**GENERAL DESCRIPTION**

Pitt Bull Primer Sprays are designed to provide a durable protective coating that resists fading, chipping and peeling and provides a sound base for topcoat adhesion. These sprays apply easily and dry fast to a tough attractive finish. Not for use on galvanized metal.

**RECOMMENDED SUBSTRATES**

Metal  
Wood

**PRODUCT DATA**

**PRODUCT TYPE:** Modified Alkyd

**PRACTICAL COVERAGE:** Approximately 10-12 sq. ft./can  
(0.90-1.10 m<sup>2</sup>/can)

**DRYING TIME:** Dry time @70-80°F (21- 27°C); 50% relative humidity.

To Touch: 20 minutes  
To Handle: 30 minutes  
To Recoat: Within 1 hour or after 24 hours

Primers may be immediately topcoated.

Drying times listed may vary depending on temperature, humidity, film build, and air movement.

**DRY HEAT RESISTANCE:** 200°F (93°C)

**CLEANUP:** Clean valve immediately after use by turning can upside down and depressing spray button for 3-5 seconds (some paint will be sprayed out, so be careful to not inadvertently spray yourself or other objects). Wipe off tip before storing. Clean up wet paint with xylene or mineral spirits.

**DANGER:** Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container. Refer to [www.ppgpittsburghpaints.com](http://www.ppgpittsburghpaints.com), Spontaneous Combustion Advisory for additional information.

**STORAGE:** STORE OUT OF DIRECT SUNLIGHT. Prevent this container from coming in contact with water for a prolonged period of time. Always keep container in a cool, dry place.

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

**FLASH POINT:** -156°F (-104°C)

**PRODUCT INFORMATION**

Primer Spray Paint

55-670 Primer Red Oxide  
55-671 Primer Gray

**PACKAGING**

Aerosol Net Wt. 12 oz. (340 g)

**DANGER! AEROSOLS EXTREMELY FLAMMABLE. MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. Read Label and Material Safety Data Sheet Prior to Use. See other cautions on last page.**

## GENERAL SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent or other suitable cleaning method. Rinse thoroughly with fresh water and allow to thoroughly dry. All surfaces must be dry at time of application. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces to create a surface profile. Top coat with Pitt-Bull 55 Series enamels.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

## APPLICATION INFORMATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Shake often during use. Hold can upright 10-12" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply two or more light coats a few minutes apart to avoid drips and runs. **Do not use near open flame.**

If valve clogs, remove spray button and clean with thinner. DO NOT stick pins or wire into can opening. Replace spray button firmly, with valve opening pointing away from you. After use, invert can and spray for 4 seconds to clean valve.

USE IN A WELL VENTILATED AREA ONLY. USE ONLY AS DIRECTED. Use outdoors or in a well ventilated area such as an open garage. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist. Do not apply to surfaces that, when heated, exceed 200°F (93°C) or galvanized metal.

### Permissible temperatures during application:

Material:	50 to 90°F	10 to 32°C
Ambient:	50 to 90°F	10 to 32°C

## LIMITATIONS OF USE

DO NOT STICK PIN OR OTHER OBJECT INTO THE CAN. Contents under pressure. DO NOT PUNCTURE, INCINERATE (BURN), COMPACT OR STORE ABOVE 120°F (49°C). STORE OUT OF DIRECT SUNLIGHT. Exposure to heat or prolonged exposure to sun may cause bursting.

Do not use on surfaces that come into contact with food.

## PRECAUTIONS

**DANGER!** AEROSOLS EXTREMELY FLAMMABLE. MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. HARMFUL IF INHALED. HARMFUL IF ABSORBED THROUGH SKIN. HARMFUL OR FATAL IF SWALLOWED. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. Sanding and grinding dusts may be harmful if inhaled. In a fire or if heated, a pressure increase will occur and the container may burst or explode. Can enter lungs and cause damage. Keep away from heat, sparks and flame. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F (48°C). Do not breathe vapor or mist. Do not swallow. Do not get on skin or clothing. Avoid contact with eyes. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH PITT BULL MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.** Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information. **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention immediately. If inhaled, remove to fresh air. Call physician immediately. Keep out of the reach of children. For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. **EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).**

The PPG logo is a registered trademark and PPG Paints is a trademark of PPG Industries Ohio, Inc. Pitt Bull is a registered trademark of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-441-9695.



PPG Industries, Inc.  
Architectural Coatings  
One PPG Place  
Pittsburgh, PA 15272  
[www.ppgpaints.com](http://www.ppgpaints.com)

Technical Services  
1-800-441-9695  
1-888-807-5123 fax

Architect/Specifier  
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.  
2505, rue de la Metropole  
Longueuil (Quebec) Canada J4G 1E5

T.D. 55-670,671  
11/2015

Made in the  
**USA**