

# SUA066\_A2

## Safety Data Sheet INTERFINE 5703 RED BASE



Bulk Sales Reference No.: SUA066  
SDS Revision Date: 01/16/2019  
SDS Revision Number: A2-7

### 1. Identification of the preparation and company

#### 1.1. Product identifier

Product Identity INTERFINE 5703 RED BASE  
Bulk Sales Reference No. SUA066

1.2. Relevant identified uses of the substance or mixture and uses advised against  
Intended Use See Technical Data Sheet.

#### 1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC  
Manufacturer:  
Akzo Nobel Coatings  
International Paint  
6001 Antoine Drive  
Houston, Texas 77091

Emergency  
CHEMTREC (800) 424-9300  
International Paint (713) 682-1711  
Poison Control Center (800) 854-6813  
Customer Service  
International Paint (800) 589-1267  
Fax No. (800) 631-7481

### 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.  
Skin Irrit. 3;H316 Causes mild skin irritation.  
Skin Sens. 1;H317 May cause an allergic skin reaction.  
Carc. 2;H351 Suspected of causing cancer.  
Repr. 2;H361D Suspected of damaging the unborn child.  
Aquatic Chronic 3;H412 Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Warning.

H226 Flammable liquid and vapor.  
H316 Causes mild skin irritation.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.

## SUA066\_A2

H361 Suspected of damaging fertility or the unborn child.

H412 Harmful to aquatic life with long lasting effects.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P235 Keep cool.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe mist / vapors / spray.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+352 IF ON SKIN: Wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P308+313 IF exposed or concerned: Get medical advice/attention.

P331 Do NOT induce vomiting.

P332+313 If skin irritation occurs: Get medical advice/attention.

P333 If skin irritation or a rash occurs:.

P363 Wash contaminated clothing before reuse.

P370 In case of fire: Use water spray, fog, or regular foam..

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating

Health: 2\*

Flammability: 3

Reactivity: 0

3. Composition/information on ingredients
---

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Barium sulfate CAS Number: 0007727-43-7	25 - 50	Not Classified	[1][2]
Methyl Amyl Ketone CAS Number: 0000110-43-0	10 - 25	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H302	[1][2]
Solvent naphtha (petroleum), light aromatic CAS Number: 0064742-95-6	1.0 - 10	Asp. Tox. 1;H304	[1]
Methoxydimethylphenylsiloxane CAS Number: 0068957-04-0	1.0 - 10	Acute Tox. 4;H302	[1]
2-Methoxy-1-Methylethyl Acetate CAS Number: 0000108-65-6	1.0 - 10	Flam. Liq. 3;H226	[1]
1,2,4-trimethyl benzene CAS Number: 0000095-63-6	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Eye Irrit. 2;H319 STOT SE 3;H335	[1]

## SUA066\_A2

		Skin Irrit. 2;H315 Aquatic Chronic 2;H411	
Xylene CAS Number: 0001330-20-7	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315	[1][2]
N-Butyl Acetate CAS Number: 0000123-86-4	1.0 - 10	Flam. Liq. 3;H226 STOT SE 3;H336	[1][2]
Kaolin CAS Number: 0001332-58-7	1.0 - 10	Not Classified	[1][2]
Styrene CAS Number: 0000100-42-5	0.10 - 1.0	Flam. Liq. 3;H226 Acute Tox. 4;H332 Skin Irrit. 2;H315 Eye Irrit. 2;H319 Repr. 2;H361D STOT RE 1;H372	[1][2]
,"Bis(pentametil-4-piperidil)sebacate","ID" CAS Number: 0041556-26-7	0.10 - 1.0	Skin Sens. 1;H317 Aquatic Chronic 1;H410 Aquatic Acute 1;H400	[1]
Methyl Ethyl Ketoxime (MEKO) CAS Number: 0000096-29-7	0.10 - 1.0	Carc. 2;H351 Acute Tox. 4;H312 Eye Dam. 1;H318 Skin Sens. 1;H317	[1]
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omeg CAS Number: 0104810-47-1	0.10 - 1.0	Skin Sens. 1;H317	[1]
Stoddard solvent CAS Number: 0008052-41-3	0.10 - 1.0	STOT RE 1;H372 Asp. Tox. 1;H304	[1][2]
Benzotriazol derivative CAS Number: 0104810-48-2	0.10 - 1.0	Skin Sens. 1;H317 Aquatic Chronic 2;H411	[1]
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester CAS Number: 0082919-37-7	0.10 - 1.0	Skin Sens. 1;H317 Aquatic Chronic 1;H410	[1]
Cobalt 2-Ethyl Hexanoate CAS Number: 0000136-52-7	0.10 - 1.0	Acute Tox. 4;H302 Skin Irrit. 2;H315 Skin Sens. 1;H317	[1]

	Aquatic Chronic 2;H411	
--	------------------------------	--

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

#### 4. First aid measures

##### 4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

##### 4.2. Most important symptoms and effects, both acute and delayed

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.

##### Chronic effects

#### 5. Fire-fighting measures

##### 5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient.

CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective.

SMALL FIRES: Use dry chemical, CO<sub>2</sub>, water spray or regular foam. LARGE FIRES: Use water spray, fog, or regular foam. Do not use straight streams. Move containers from fire area if you can do so without risk.

##### 5.2. Special hazards arising from the substance or mixture

No data available

##### 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 128

#### 6. Accidental release measures

##### 6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

##### 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

##### 6.3. Methods and material for containment and cleaning up

## SUA066\_A2

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

<b>7. Handling and storage</b>
--------------------------------

### 7.1. Precautions for safe handling

#### Handling

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

#### In Storage

Keep away from heat, sparks and flame.

### 7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Avoid contact with eyes, skin and clothing.

No data available

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

### 7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

<b>8. Exposure controls and personal protection</b>
---

### 8.1. Control parameters

#### Exposure

CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4-trimethyl benzene	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	25 ppm TWA; 125 mg/m3 TWA
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000096-29-7	Methyl Ethyl Ketoxime (MEKO)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	

SUA066\_A2

			No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000100-42-5	Styrene	OSHA	100 ppm TWA100 ppm STEL; 425 mg/m3 STEL
		ACGIH	20 ppm TWA40 ppm STEL
		NIOSH	50 ppm TWA; 215 mg/m3 TWA100 ppm STEL; 425 mg/m3 STEL700 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	35 ppm TWA100 ppm STEL
		Mexico	20 ppm TWA VLE-PPT40 ppm STEL [PPT-CT]
		Brazil	78 ppm TWA LT; 328 mg/m3 TWA LT
0000108-65-6	2-Methoxy-1-Methylethyl Acetate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	50 ppm TWA; 270 mg/m3 TWA
		Mexico	No Established Limit
		Brazil	No Established Limit
0000110-43-0	Methyl Amyl Ketone	OSHA	

SUA066\_A2

			100 ppm TWA; 465 mg/m3 TWA
		ACGIH	50 ppm TWA
		NIOSH	100 ppm TWA; 465 mg/m3 TWA800 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	25 ppm TWA; 115 mg/m3 TWA
		Mexico	50 ppm TWA VLE-PPT
		Brazil	No Established Limit
0000123-86-4	N-Butyl Acetate	OSHA	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL
		ACGIH	50 ppm TWA (listed under Butyl acetates, all isomers)150 ppm STEL (listed under Butyl acetates, all isomers)
		NIOSH	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL1700 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	150 ppm TWA200 ppm STEL
		Mexico	150 ppm TWA VLE-PPT; 710 mg/m3 TWA VLE-PPT200 ppm STEL [PPT-CT]
		Brazil	No Established Limit
0000136-52-7	Cobalt 2-Ethyl Hexanoate	OSHA	No Established Limit
		ACGIH	

			No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0001330-20-7	Xylene	OSHA	100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL
		ACGIH	100 ppm TWA150 ppm STEL
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	100 ppm TWA150 ppm STEL
		Mexico	100 ppm TWA VLE-PPT150 ppm STEL [PPT-CT]
		Brazil	78 ppm TWA LT; 340 mg/m3 TWA LT
0001332-58-7	Kaolin	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	2 mg/m3 TWA (particulate matter containing no asbestos and
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	No Established Limit



		OHSA, CAN	2 mg/m3 TWA (containing no Asbestos and
		Mexico	2 mg/m3 TWA VLE-PPT (particulate matter containing no asbestos and
		Brazil	No Established Limit
0007727-43-7	Barium sulfate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	5 mg/m3 TWA (inhalable particulate matter, particulate matter containing no asbestos and
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	5 mg/m3 TWA (particulate matter containing no Asbestos and
		Mexico	10 mg/m3 TWA VLE-PPT
		Brazil	No Established Limit
0008052-41-3	Stoddard solvent	OSHA	500 ppm TWA; 2900 mg/m3 TWA
		ACGIH	100 ppm TWA
		NIOSH	350 mg/m3 TWA 1800 mg/m3 Ceiling (15 min) 20000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA,	525 mg/m3

SUA066\_A2

		CAN	TWA (140C Flash aliphatic solvent)
		Mexico	100 ppm TWA VLE-PPT
		Brazil	No Established Limit
0041556-26-7	"Bis(pentametil-4-piperidil)sebacate", "ID"	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0064742-95-6	Solvent naphtha (petroleum), light aromatic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0068957-04-0	Methoxydimethylphenylsiloxane	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

SUA066\_A2

		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0082919-37-7	Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0104810-47-1	Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omeg	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0104810-48-2	Benzotriazol derivative	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established

## SUA066\_A2

			Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

## Health Data

CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4-trimethyl benzene	NIOSH	No Established Limit
0000096-29-7	Methyl Ethyl Ketoxime (MEKO)	NIOSH	No Established Limit
0000100-42-5	Styrene	NIOSH	Nervous system effects; eye and respiratory system irritation; reproductive system effects
0000108-65-6	2-Methoxy-1-Methylethyl Acetate	NIOSH	No Established Limit
0000110-43-0	Methyl Amyl Ketone	NIOSH	Irritation; liver kidney
0000123-86-4	N-Butyl Acetate	NIOSH	Mucous membrane and eye irritation; high concentrations cause nervous system effects in animals
0000136-52-7	Cobalt 2-Ethyl Hexanoate	NIOSH	No Established Limit
0001330-20-7	Xylene	NIOSH	Central nervous system depressant; respiratory and eye irritation
0001332-58-7	Kaolin	NIOSH	Skin and mucous membrane injury respiratory effects
0007727-43-7	Barium sulfate	NIOSH	Eye nose
0008052-41-3	Stoddard solvent	NIOSH	Eye nose
0041556-26-7	"Bis(pentametil-4-piperidil)sebacate", "ID"	NIOSH	No Established Limit
0064742-95-6	Solvent naphtha (petroleum), light aromatic	NIOSH	No Established Limit
0068957-04-0	Methoxydimethylphenylsiloxane	NIOSH	No Established Limit
0082919-37-7	Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidiny ester	NIOSH	No Established Limit
0104810-47-1	Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omeg	NIOSH	No Established Limit
0104810-48-2	Benzotriazol derivative	NIOSH	No Established Limit

## Carcinogen Data

CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4-trimethyl benzene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000096-29-7	Methyl Ethyl Ketoxime (MEKO)	OSHA	Select Carcinogen: No

## SUA066\_A2

		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000100-42-5	Styrene	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: Yes
		IARC	Group 1: No; Group 2a: Yes; Group 2b: No; Group 3: No; Group 4: No;
0000108-65-6	2-Methoxy-1-Methylethyl Acetate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000110-43-0	Methyl Amyl Ketone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000123-86-4	N-Butyl Acetate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000136-52-7	Cobalt 2-Ethyl Hexanoate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001330-20-7	Xylene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0001332-58-7	Kaolin	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007727-43-7	Barium sulfate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0008052-41-3	Stoddard solvent	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0041556-26-7	"Bis(pentametil-4-piperidil)sebacate", "ID"	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-95-6	Solvent naphtha (petroleum), light aromatic	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0068957-04-0	Methoxydimethylphenylsiloxane	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No

SUA066\_A2

		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0082919-37-7	Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0104810-47-1	Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omeg	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0104810-48-2	Benzotriazol derivative	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Appearance	Coloured Liquid
Odor threshold	Not Measured
pH	No Established Limit
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	64 (°C) 148 (°F)
Flash Point	39 (°C) 102 (°F)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1 Upper Explosive Limit: No Established Limit
vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than air

## SUA066\_A2

Specific Gravity	1.27
Solubility in Water	Not Measured
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	No Established Limit Not Measured
VOC %	Refer to the Technical Data Sheet or label where information is available.
VOHAP content (gm/litre of paint)	87.47 (as supplied)
VOHAP content (gm/litre of Solid Coating)	54.61 (as supplied)

<b>10. Stability and reactivity</b>
-------------------------------------

10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

<b>11. Toxicological information</b>
--------------------------------------

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr
Barium sulfate - (7727-43-7)	3,000.00, Mouse - Category: 5	No data available	No data available	No data available
Methyl Amyl Ketone - (110-43-0)	1,670.00, Rat - Category: 4	12,600.00, Rat - Category: NA	No data available	No data available
Solvent naphtha (petroleum), light aromatic - (64742-95-6)	6,800.00, Rat - Category: NA	3,400.00, Rabbit - Category: 5	No data available	No data available
Methoxydimethylphenylsiloxane - (68957-04-0)	No data available	No data available	No data available	No data available
2-Methoxy-1-Methylethyl Acetate - (108-65-6)	6,190.00, Rat - Category: NA	2,001.00, Rabbit - Category: 5	No data available	No data available
1,2,4-trimethyl benzene - (95-63-6)	3,400.00, Rat - Category: 5	3,160.00, Rabbit - Category: 5	18.00, Rat - Category: 4	No data available

## SUA066\_A2

Xylene - (1330-20-7)	4,299.00, Rat - Category: 5	1,548.00, Rabbit - Category: 4	No data available	20.00, Rat - Category: NA
N-Butyl Acetate - (123-86-4)	10,760.00, Rat - Category: NA	17,600.00, Rabbit - Category: NA	No data available	No data availabl
Kaolin - (1332-58-7)	No data available	No data available	No data available	No data availabl
Styrene - (100-42-5)	2,650.00, Rat - Category: 5	No data available	12.00, Rat - Category: 4	No data availabl
, "Bis(pentametil-4-piperidil)sebacate", "ID" - (41556-26-7)	5,001.00, Rat - Category: NA	2,001.00, Rat - Category: 5	No data available	No data availabl
Methyl Ethyl Ketoxime (MEKO) - (96-29-7)	2,236.00, Rat - Category: 5	1,001.00, Rabbit - Category: 4	No data available	No data availabl
Poly(oxy-1,2-ethanediy), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omeg - (104810-47-1)	No data available	No data available	No data available	No data availabl
Stoddard solvent - (8052-41-3)	5,001.00, Rat - Category: NA	No data available	No data available	5.50, Rat - Category: NA
Benzotriazol derivative - (104810-48-2)	2,000.00, Rat - Category: 4	2,000.00, Rat - Category: 4	No data available	No data availabl
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester - (82919-37-7)	No data available	No data available	No data available	No data availabl
Cobalt 2-Ethyl Hexanoate - (136-52-7)	1,220.00, Rabbit - Category: 4	5,000.00, Rat - Category: 5	No data available	No data availabl

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation.
Eye damage/irritation	Not Classified	Not Applicable
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	2	Suspected of causing cancer.
Reproductive Toxicity	2	Suspected of damaging the unborn child.
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

## 12. Ecological information

## 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.



SUA066\_A2

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	
Barium sulfate - (7727-43-7)	59,000.00, Poecilia sphenops	32.00, Daphnia magna	
Methyl Amyl Ketone - (110-43-0)	131.00, Pimephales promelas	90.20, Daphnia magna	98.20
Solvent naphtha (petroleum), light aromatic - (64742-95-6)	9.22, Oncorhynchus mykiss	6.14, Daphnia magna	1
Methoxydimethylphenylsiloxane - (68957-04-0)	Not Available	Not Available	
2-Methoxy-1-Methylethyl Acetate - (108-65-6)	100.00, Oncorhynchus mykiss	501.00, Daphnia magna	1,001.0
1,2,4-trimethyl benzene - (95-63-6)	7.72, Pimephales promelas	3.60, Daphnia magna	2.
Xylene - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.
N-Butyl Acetate - (123-86-4)	18.00, Pimephales promelas	44.00, Daphnia sp	246.0
Kaolin - (1332-58-7)	Not Available	Not Available	
Styrene - (100-42-5)	4.08, Pimephales promelas	4.70, Daphnia magna	
,"Bis(pentametil-4-piperidil)sebacate", "ID" - (41556-26-7)	1.00, Lepomis macrochirus	20.00, Daphnia magna	
Methyl Ethyl Ketoxime (MEKO) - (96-29-7)	320.00, Leuciscus idus	500.00, Daphnia magna	83
Poly(oxy-1,2-ethanediy), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omeg - (104810-47-1)	Not Available	Not Available	
Stoddard solvent - (8052-41-3)	Not Available	Not Available	
Benzotriazol derivative - (104810-48-2)	2.80, Pisces	3.80, Daphnia magna	
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidiny ester - (82919-37-7)	Not Available	Not Available	
Cobalt 2-Ethyl Hexanoate - (136-52-7)	Not Available	Not Available	

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

14.1. UN number UN 1263

14.2. UN proper shipping name PAINT

## SUA066\_A2

### 14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)		IMO / IMDG (Ocean Transportation)	
Proper Shipping Name	PAINT	IMDG Proper Shipping Name	PAINT
Hazard Class	3 - Flammable	IMDG Hazard Class Sub Class	3 - Flammable Not applicable
UN / NA Number	UN 1263		
Packing Group	III	IMDG Packing Group	III
CERCLA/DOT RQ	547 gal. / 5762 lbs.	System Reference Code	2

14.4. Packing group III

### 14.5. Environmental hazards

IMDG Marine Pollutant: No

### 14.6. Special precautions for user

Not Applicable

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information
----------------------------

**Regulatory Overview** The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

**WHMIS Classification** B3 D2A

**DOT Marine Pollutants (10%):**  
(No Product Ingredients Listed)

**DOT Severe Marine Pollutants (1%):**  
(No Product Ingredients Listed)

**EPCRA 311/312 Chemicals and RQs (>.1%) :**

N-Butyl Acetate (5000 lb final RQ (listed under Butyl acetate); 2270 kg final RQ (listed under Butyl acetate))

Ethyl Benzene (1000 lb final RQ; 454 kg final RQ)

m-xylene (1000 lb final RQ; 454 kg final RQ)

o-Xylene (1000 lb final RQ; 454 kg final RQ)

p-Xylene (100 lb final RQ; 45.4 kg final RQ)

Styrene (1000 lb final RQ; 454 kg final RQ)

Xylene (100 lb final RQ; 45.4 kg final RQ)

**EPCRA 302 Extremely Hazardous (>.1%) :**  
(No Product Ingredients Listed)

**EPCRA 313 Toxic Chemicals (>.1%) :**

1,2,4-trimethyl benzene

Ethyl Benzene

m-xylene

o-Xylene

p-Xylene

Styrene

Xylene

**Mass RTK Substances (>1%) :**

1,2,4-trimethyl benzene

Barium sulfate

N-Butyl Acetate

Kaolin

Methyl Amyl Ketone

Xylene

## Penn RTK Substances (&gt;1%) :

1,2,4-trimethyl benzene  
Barium sulfate  
N-Butyl Acetate  
Kaolin  
Methyl Amyl Ketone  
Xylene

Penn Special Hazardous Substances (>.01%) :  
(No Product Ingredients Listed)

RCRA Status:  
(No Product Ingredients Listed)

## N.J. RTK Substances (&gt;1%) :

1,2,4-trimethyl benzene  
Barium sulfate  
N-Butyl Acetate  
Kaolin  
Methyl Amyl Ketone  
Xylene

## N.J. Special Hazardous Substances (&gt;.01%) :

2-Butoxy-ethanol  
Cumene  
N-Butyl Acetate  
Acrilato de n-butilo  
Crystalline Silica - Quartz  
Ethanol  
Ethyl Benzene  
m-xylene  
Methanol  
Propenoic acid, 2-methyl-, methyl ester  
Methyl Propyl Ketone  
o-Xylene  
p-Xylene  
Styrene  
Xylene

## N.J. Env. Hazardous Substances (&gt;.1%) :

1,2,4-trimethyl benzene  
Ethyl Benzene  
m-xylene  
o-Xylene  
p-Xylene  
Styrene  
Xylene

## Proposition 65 - Carcinogens (&gt;0%):

Ethanol  
Cumene  
Ethyl Benzene  
Styrene

Proposition 65 - Female Repro Toxins (>0%):  
(No Product Ingredients Listed)Proposition 65 - Male Repro Toxins (>0%):  
(No Product Ingredients Listed)

## Proposition 65 - Developmental Toxins (&gt;0%):

Ethanol  
Methanol

16. Other information
-----------------------

## SUA066\_A2

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H226 Flammable liquid and vapor.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H361D Suspected of damaging the unborn child.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.

The following sections have changed since the previous revision.

SECTION 2: Hazards identification  
SECTION 3: Composition/information on ingredients  
SECTION 4: First aid measures  
SECTION 5: Fire-fighting measures  
SECTION 9: Physical and chemical properties  
SECTION 10: Stability and reactivity  
SECTION 11: Toxicological information  
SECTION 12: Ecological information  
SECTION 14: Transport information

End of Document